



Reader

Product Code: L-RX400

Description: Reader USB

The Reader interface to the personal computer via a standard USB cable (incorporated into the reader). One of the features of this reader is that it operates on a plug and play basis due to the USB standard it complies to.

The reader works in conjunction with the Wavetrend Active RF ID Tags. The enclosure was designed in such a way that it enhances the esthetical value of that individual's desk.

The user is able to select only one tag via software and monitor that specific tag, or monitor a few tags, which was selected by the user at installation.



Features

- The reader gain can be adjusted from high to low gain mode dynamically via software.
- The reader is completely plug and play.
- The reader complies with all the USB 1.1 standards. Meaning it can interface to any USB hub etc.
- In stand-alone mode the RSSI setting can be set dynamically via software. Which controls the read-range of the reader.
- The user receives a working DLL to interface to the reader. This then simplifies interfacing on software level to hardware, which makes the reader very transparent.

Applications

PCAC

- The reader can be used for the Wavetrend PCAC system.

STAND ALONE READER

- The reader may be used as a general reader were there is but only a personal computer with USB port and no RS-485 network nearby.





L-Series

Product Information Sheet



Specification

Environmental

Operational temperature - 10° C to + 60° C
Storage temperature - 20° C to + 70° C

Physical

Size 81 mm x 57 mm x 20 mm (Oval Enclosure)
Weight Approx. 72 gms
Colour Ice Blue (Clariant 04-600 1%)
Type of material Fire resistant ABS

RF Specifications

Frequency 433 Mhz
Typical Reception Range 8 Meters (24 feet)

Certification

This device complies with all the necessary rules and regulations needed. For further information please check the back of the reader for FCC and CE numbers or contact Wavetrend Technologies.



Wavetrend (UK) Ltd
Parkshot House
5 Kew Road
Richmond
Surrey
TW9 2PR
England
Tel +44 (0) 20 8334 8400
Fax +44 (0) 20 8334 8401
www.wavetrend.net
sales-uk@wavetrend.net



Wavetrend Technologies, Inc.
13912 NE 31st Place
Bellevue
WA 98005
USA
Tel +1 425 785 4781
Fax +1 425 869 4150
www.wavetrend.net
sales-usa@wavetrend.net



Wavetrend (Pty) Ltd
Wavetrend House
Hammets Crossing Office Park
Selborne Rd
Fourways
Johannesburg
South Africa
Tel +27 (11) 462 2633
Fax +27 (11) 462 6316
www.wavetrend.net
sales-sa@wavetrend.net



Document No.
EAB-00900-03-PI

Product No.
L-RX400

Wavetrend Technologies
Reader USB

Date
2005/04/21

Page
2 of 2

